

# RM1500 with REEFE® RPS036 / 050

RM SYSTEMS

The RM1500 with RPS series is designed for speed of installation with integrated pressure controller, no solenoid valve or electronic controls. This system stops main supply while the rain water is being pumped to help conserve our precious resource. When in mains status it provides full pressure and full flow. Covered by a two year in-field warranty.

| CODE  | DESCRIPTION   | NO. OF TAPS | MAXIMUM  |              |       | CABLE | OUTLET |     |    |
|-------|---|-------------|----------|--------------|-------|-------|--------|-----|----|
|       |   |             | HEAD (M) | FLOW (L/MIN) | POWER |       |        |     |    |
|       |   |             |          |              | KW    | VOLT  | HP     |     |    |
| 12895 | RM1500 with REEFE® RPS036 Submersible Pressure Pump | 4 - 6       | 36       | 82LPM        | 0.37  | 240   | 0.5    | 10m | 1" |
| 12948 | RM1500 with REEFE® RPS050 Submersible Pressure Pump | 6 - 9       | 50       | 86LPM        | 0.8   | 240   | 1.1    | 10m | 1" |

## APPLICATIONS

- Whole house supply up to 6 bathrooms
- Toilet blocks\*
- Garden Irrigation\*
- Ablutions blocks\*
- Hotels & motels\*
- Factories & warehouses\*
- Units & complexes\*
- Council parks irrigation\*

## FEATURES & BENEFITS

- Watermark certified componentry
- This system automatically checks for rainwater periodically. If there is no tank supply, the mains supply flows.
- Simply plug in - no electrician required
- Affordable solution for new and old installations
- Pump has integrated pressure controller with auto re-start and run dry protection.
- Compact Design with water cooled motor
- Corrosion resistant
- Base ensures suction inlet is out of sludge build up

## CONSTRUCTION

- Gr 304 stainless steel casing and shaft
- Plastic Impellers and Diffusers
- 10m Power Cable
- Plastic Pump Base and Discharge Body
- RM1500: Chrome plated brass
- RPS036: 5 Impellers. RPS050: 7 Impellers.

\* Check specifications required.

